

(12) UK Patent Application (19) GB (11) 2 377 996 (13) A

(43) Date of Printing by UK Office 29.01.2003

(21) Application No 0216235.2

(22) Date of Filing 10.01.2001

(30) Priority Data

(31) 60175585 (32) 11.01.2000 (33) US
(31) 09754431 (32) 04.01.2001

(86) International Application Data

PCT/US2001/000742 En 10.01.2001

(87) International Publication Data

WO2001/051880 En 19.07.2001

(51) INT CL⁷

G01V 3/20

(52) UK CL (Edition V)

G1N NCLJ N19B2Q

(56) Documents Cited by ISA

NOT YET ADVISED

NOT YET ADVISED

(58) Field of Search by ISA

Other: NOT YET ADVISED

(71) Applicant(s)

Baker Hughes Incorporated
(Incorporated in USA - Delaware)
3900 Essex Lane, Suite 1200, Houston,
Texas 77027, United States of America

(74) Agent and/or Address for Service

Haseltine Lake & Co
Imperial House, 15-19 Kingsway,
LONDON, WC2B 6UD, United Kingdom


(72) Inventor(s)

Martin T Evans
Richard A Burt

(54) Abstract Title

An image focusing method and apparatus for wellbore resistivity imaging

(57) An apparatus for obtaining resistivity images of a borehole includes an array of measure electrodes separated from a pad or the body of the instrument by a guard electrode. The guard electrode is maintained at a slightly lower potential than the pad and the measure electrode is at an intermediate potential thereto. With this arrangement, the current from the guard electrode defocuses the measure current from the measure electrode as it enters the formation, and at greater distances, the current from the measure electrode is refocused by the effect of the current from the pad. This defocusing and refocusing defines a region of investigation away from the borehole wall that is relatively insensitive to borehole rugosity. Circumferential and vertical overlap may be obtained either by the arrangement of the measure electrodes, or by relying on the broadening of the measure beam as it enters the formation.



GB 2 377 996 A